



TE ALTERNATIVE FOR TE · AV12F10E124Q04

AV12F10E112Q04

AV12 SPM 0.1A/24VDC WHITE LED 12

<p>TE</p> <h2>AV12F10E112Q04</h2>  <p>Series AV12 · Anti-Vandal, Illuminated AV12 SPM 0.1A/24VDC WHITE LED 12</p>	<p>TE</p> <h2>AV12F10E124Q04</h2>  <p>Series AV12 · Anti-Vandal, Illuminated AV12 SPM 0.1A/24VDC WHITE LED 24</p>
---	--

100% Recommended drop-in alternative
11/12 attributes align across the parametric spec.



OPEN LIVE

WHY THIS MATCH

8 attributes align (Termination, Illumination, Circuit, Current Rating). Differences highlighted in orange.

ATTRIBUTE COMPARISON

ATTRIBUTE	TE - AV12F10E112Q04	TE - AV12F10E124Q04
Type	Anti-Vandal, Illuminated	Anti-Vandal, Illuminated
Circuit	SPST	SPST
Switch Function	Off-On	Off-On
Current Rating	1A (AC)	1A (AC)
Voltage DC	24 V	24 V
Voltage AC	—	—
Illumination	LED, White	LED, White
Termination	Solder Lug	Solder Lug
Actuator	Round, Button	Round, Button
Ingress Protection	IP67 - Dust Tight, Waterproof	IP67 - Dust Tight, Waterproof
Operating Temp	-20°C ~ 55°C	-20°C ~ 55°C
Panel Cutout	Circular - 12.20mm Dia	Circular - 12.20mm Dia