

TE ALTERNATIVE FOR TE · AV12F10E512Q04

# AV12F10E512Q04

AV12 SPM 0.1A/24VDC YELLOW LED 1

<p><b>TE</b></p> <p><b>AV12F10E512Q04</b></p>  <p>Series AV12 · Anti-Vandal, Illuminated AV12 SPM 0.1A/24VDC YELLOW LED 1</p>	<p><b>TE</b></p> <p><b>AV12F10E512Q04</b></p>  <p>Series AV12 · Anti-Vandal, Illuminated AV12 SPM 0.1A/24VDC YELLOW LED 1</p>
--	---

**100%** Recommended drop-in alternative  
11/12 attributes align across the parametric spec.



OPEN LIVE

### WHY THIS MATCH

8 attributes align (Termination, Illumination, Circuit, Current Rating). Differences highlighted in orange.

## ATTRIBUTE COMPARISON

ATTRIBUTE	TE - AV12F10E512Q04	TE - AV12F10E512Q04
Type	Anti-Vandal, Illuminated	Anti-Vandal, Illuminated
Circuit	SPST	SPST
Switch Function	Off-On	Off-On
Current Rating	1A (AC)	1A (AC)
Voltage DC	24 V	24 V
Voltage AC	—	—
Illumination	LED, Yellow	LED, Yellow
Termination	Solder Lug	Solder Lug
Actuator	Round, Button	Round, Button
Ingress Protection	IP67 - Dust Tight, Waterproof	IP67 - Dust Tight, Waterproof
Operating Temp	-20°C ~ 55°C	-20°C ~ 55°C
Panel Cutout	Circular - 12.20mm Dia	Circular - 12.20mm Dia