

TE ALTERNATIVE FOR TE · AV12F10EA12Q04

# AV12F10EA12Q04

AV12 SPM 0.1A/24VDC R&G LED 12V

<p><b>TE</b></p> <h2>AV12F10EA12Q04</h2>  <p>Series AV12 · Anti-Vandal, Illuminated AV12 SPM 0.1A/24VDC R&amp;G LED 12V</p>	<p><b>TE</b></p> <h2>AV12F10EA12Q04</h2>  <p>Series AV12 · Anti-Vandal, Illuminated AV12 SPM 0.1A/24VDC R&amp;G LED 12V</p>
--	---

**100%** Recommended drop-in alternative  
11/12 attributes align across the parametric spec.



OPEN LIVE

### WHY THIS MATCH

8 attributes align (Termination, Illumination, Circuit, Current Rating). Differences highlighted in orange.

## ATTRIBUTE COMPARISON

ATTRIBUTE	TE - AV12F10EA12Q04	TE - AV12F10EA12Q04
Type	Anti-Vandal, Illuminated	Anti-Vandal, Illuminated
Circuit	SPST	SPST
Switch Function	Off-On	Off-On
Current Rating	1A (AC)	1A (AC)
Voltage DC	24 V	24 V
Voltage AC	—	—
Illumination	LED, Green/Red	LED, Green/Red
Termination	Solder Lug	Solder Lug
Actuator	Round, Button	Round, Button
Ingress Protection	IP67 - Dust Tight, Waterproof	IP67 - Dust Tight, Waterproof
Operating Temp	-20°C ~ 55°C	-20°C ~ 55°C
Panel Cutout	Circular - 12.20mm Dia	Circular - 12.20mm Dia